LIGHTING FIXTURE
INSTALLATION INSTRUCTION

IMPORTANT:
FOR A SAFE AND SECURE INSTALLATION, THESE FIXTURES MUST BE INSTALLED BY MEANS OF SUPPORTS THAT ARE INDEPENDENT OF THE OUTLET BOX.

HANGING THE FIXTURE

1. Shut off the power at the circuit breaker and removed old fixtures from ceiling, including the old crossbar.
2. Carefully unpack new fixture and lay all the parts on a clear surface.
3. Thread top nipple into coupling until tight.
4. Place column over top nipple and secure with hex nut; place small cap over top nipple and secure with loop.
5. Thread tube into coupling until tight, then thread nipple into tube until tight.
6. Place decorative cap and cap over nipple secure with finial.
7. Place glass and candle cover over socket, then secure with socket ring.


CONNECTING THE WIRES

8. Take the black wire from the ceiling junction box and the smooth wire leg from the fixture and twist bare ends together. Twist wire connector onto the end of wires until snug.
9. Repeat same process with white junction box white and ribbed wire leg of fixture wire. NOTE: Twist wires together in the same direction as you twist the wire connector onto wires.
10. If your junction box has grounding wire (green or bare copper), attach this wire and the bare copper wire from the fixture. If junction box has no ground wire, attach the bare copper fixture wire to the junction box with a screw.
11. Tuck these wire connections neatly into the ceiling outlet box and then raise the canopy all the way to the ceiling. Thread onto ceiling loop protruding through canopy.
12. Install the light bulbs in accordance with the fixtures specifications.


NOTE: DO NOT EXCEED THE SPECIFIED WATTAGE.

Your installation is now complete. Return power to the junction box and test the fixture.

32113



32114



CSA017506HAMT1